



T-43-15-00


LS15

54LS15/DM74LS15 Triple 3-Input AND Gate with Open-Collector Outputs

General Description

This device contains three independent gates, each of which perform the logic AND function. The outputs are open-collector.

Connection Diagram



TL/F/10167-1

Order Number 54LS15DMQB, 54LS15FMQB,
DM74LS15M or DM74LS15N
See NS Package Number J14A, M14A, N14A or W14B



LS15

Absolute Maximum Ratings (Note)

T-43-15

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Note: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Supply Voltage	7V
Input Voltage	7V
Operating Free Air Temperature Range	
54LS	-55°C to +125°C
DM74LS	0°C to +70°C
Storage Temperature Range	-65°C to +150°C

Recommended Operating Conditions at $V_{CC} = +5.0V, T_A = +25°C$

Symbol	Parameter	54LS15			DM74LS15			Units
		Min	Nom	Max	Min	Nom	Max	
V_{CC}	Supply Voltage	4.5	5	5.5	4.75	5	5.25	V
V_{IH}	High Level Input Voltage	2			2			V
V_{IL}	Low Level Input Voltage			0.7			0.8	V
V_{OH}	High Level Output Voltage			5.5			5.5	V
I_{OL}	Low Level Output Current			4			8	mA
T_A	Free Air Operating Temperature	-55		125	0		70	°C

Electrical Characteristics over recommended operating free air temperature range (unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ (Note 1)	Max	Units
V_I	Input Clamp Voltage	$V_{CC} = \text{Min}, I_I = -18 \text{ mA}$			-1.5	V
V_{OL}	Low Level Output Voltage	$V_{CC} = \text{Min}, I_{OL} = \text{Max}, V_{IH} = \text{Min}$	54LS		0.4	V
			DM74		0.5	
		$I_{OL} = 4 \text{ mA}, V_{CC} = \text{Min}$	DM74		0.4	
I_I	Input Current @ Max Input Voltage	$V_{CC} = \text{Max}, V_I = 10V$			0.1	mA
I_{IH}	High Level Input Current	$V_{CC} = \text{Max}, V_I = 2.7V$			20	μA
I_{IL}	Low Level Input Current	$V_{CC} = \text{Max}, V_I = 0.4V$			-0.4	mA
I_{OH}	High Level Output Current	$V_{CC} = \text{Max}, V_O = 5.5V$			100	μA
I_{CCH}	Supply Current with Outputs High	$V_{CC} = \text{Max}, V_{IN} = \text{OPEN}$			3.6	mA
I_{CCL}	Supply Current with Outputs Low	$V_{IN} = \text{GND}$			6.6	mA

Note 1: All typicals are at $V_{CC} = 5V, T_A = 25°C$.

LS15

Switching Characteristics

T-43-15

V_{CC} = +5.0V, T_A = +25°C (See Section 1 for test waveforms and output load)

Symbol	Parameter	R _L = 2 kΩ C _L = 15 pF		Units
		Max		
		54LS	DM74	
t _{PLH}	Propagation Delay Time Low to High Level Output	24	20	ns
t _{PHL}	Propagation Delay Time High to Low Level Output	18	14	ns

2