



MOTOROLA


Dual 4-Input Positive AND Gate

ELECTRICALLY TESTED PER:
MIL-M-38510/31003


Military 54LS21




LOGIC DIAGRAM



AC TEST CIRCUIT



WAVEFORMS



AVAILABLE AS:

- 1) JAN: JM38510/31003BXA
- 2) SMD: N/A
- 3) 883: 54LS21/BXAJC

X = CASE OUTLINE AS FOLLOWS:
PACKAGE: CERDIP: C
CERFLAT: D
LCC: 2

THE LETTER "M" APPEARS
BEFORE THE / ON LCC.

5

PIN ASSIGNMENTS

FUNCT.	DIL 632-08	FLATS 717-04	LCC 756A-02	BURN-IN (COND. A)
A1	1	1	2	V _{CC}
B1	2	2	3	V _{CC}
NC	3	3	4	V _{CC}
C1	4	4	6	V _{CC}
D1	5	5	8	V _{CC}
Y1	6	6	9	V _{CC}
GND	7	7	10	GND
Y2	8	8	12	V _{CC}
A2	9	9	13	V _{CC}
B2	10	10	14	V _{CC}
NC	11	11	16	V _{CC}
C2	12	12	18	V _{CC}
D2	13	13	19	V _{CC}
V _{CC}	14	14	20	V _{CC}

BURN-IN CONDITIONS:

V_{CC} = 5.0 V MIN/6.0 V MAX

NOTES:

1. Pulse generator has the following characteristics: $t_r \leq 15$ ns, $t_f \leq 6.0$ ns, $t_p = 0.5$ μ s, PRR ≤ 1.0 MHz, and $Z_{OUT} \approx 50 \Omega$.
2. Terminal conditions (pins not designated) may be high ≥ 2.0 V, low ≤ 0.7 V, or open.
3. $C_L = 50$ pF $\pm 10\%$, including scope probe, wiring and stray capacitance.
4. $R_L = 2.0$ k Ω $\pm 5.0\%$.
5. All diodes are 1N3064 or equivalent.
6. Voltage measurements are to be made with respect to network ground terminal.

Symbol	Parameter	Limits						Unit	Test Condition (Unless Otherwise Specified)		
		+ 25°C		+ 125°C		- 55°C					
	Static Parameters:	Subgroup 1		Subgroup 2		Subgroup 3					
		Min	Max	Min	Max	Min	Max				
V _{OH}	Logical "1" Output Voltage	2.5		2.5		2.5		V	V _{CC} = 4.5 V, I _{OL} = - 400 μA, V _{IH} = 2.0 V, other inputs = 2.0 V.		
V _{OL}	Logical "0" Output Voltage		0.4		0.4		0.4	V	V _{CC} = 4.5 V, I _{OL} = 4.0 mA, V _{IL} = 0.7 V, other inputs = 5.5 V.		
V _{IC}	Input Clamping Voltage		- 1.5					V	V _{CC} = 4.5 V, I _{IN} = - 18 mA, other inputs are open.		
I _{IH1}	Logical "1" Input Current		20		20		20	μA	V _{CC} = 5.5 V, V _{IN} = 2.7 V, other inputs = 0 V.		
I _{IH2}	Logical "1" Input Current		100		100		100	μA	V _{CC} = 5.5 V, V _{IN} = 5.5 V, other inputs = 0 V.		
I _{IL}	Logical "0" Input Current	- 150	- 380	- 150	- 380	- 150	- 380	μA	V _{CC} = 5.5 V, V _{IN} = 0.4 V, other inputs = 5.5 V.		
I _{OS}	Output Short Circuit Current	- 15	- 110	- 15	- 110	- 15	- 110	mA	V _{CC} = 5.5 V, V _{IN} = 5.5 V (all inputs), V _{OUT} = 0 V.		
I _{ICCH}	Power Supply Current		2.4		2.4		2.4	mA	V _{CC} = 5.5 V, V _{IN} = 5.5 V (all inputs).		
I _{ICCL}	Power Supply Current		4.4		4.4		4.4	mA	V _{CC} = 5.5 V, V _{IN} = 0 V (all inputs).		
V _{IH}	Logical "1" Input Voltage	2.0		2.0		2.0		V	V _{CC} = 4.5 V.		
V _{IL}	Logical "0" Input Voltage		0.7		0.7		0.7	V	V _{CC} = 4.5 V.		
	Functional Tests	Subgroup 7		Subgroup 8A		Subgroup 8B			per Truth Table with V _{CC} = 5.0 V, V _{INL} = 0.5 V, and V _{INH} = 2.5 V.		

5

Symbol	Parameter	Limits						Unit	Test Condition (Unless Otherwise Specified)		
		+ 25°C		+ 125°C		- 55°C					
	Switching Parameters:	Subgroup 9		Subgroup 10		Subgroup 11					
		Min	Max	Min	Max	Min	Max				
t _{PHL} t _{PLH}	Propagation Delay /Data-Output Output High-Low	2.0 —	20 20	2.0 —	30 25	2.0 —	30 25	ns	V _{CC} = 5.0 V, C _L = 50 pF, R _L = 2.0 kΩ. V _{CC} = 5.0 V, C _L = 15 pF, R _L = 2.0 kΩ.		
t _{PLH} t _{PHL}	Propagation Delay /Data-Output Output Low-High	2.0 —	15 15	2.0 —	25 20	2.0 —	25 20	ns	V _{CC} = 5.0 V, C _L = 50 pF, R _L = 2.0 kΩ. V _{CC} = 5.0 V, C _L = 15 pF, R _L = 2.0 kΩ.		

NOTES:

1. The limits specified for C_L = 15 pF are guaranteed but not tested.