

74F114

Dual JK Negative Edge-Triggered Flip-Flop with Common Clocks and Clears

General Description

The 'F114 contains two high-speed JK flip-flops with common Clock and Clear inputs. Synchronous state changes are initiated by the falling edge of the clock. Triggering occurs at a voltage level of the clock and is not directly related to the transition time. The J and K inputs can change when the clock is in either state without affecting the flip-flop, provided that they are in the desired state during the recommended setup and hold times relative to the falling edge of the clock. A LOW signal on \bar{S}_D or \bar{C}_D prevents clocking and forces Q or \bar{Q} HIGH, respectively. Simultaneous LOW signals on \bar{S}_D and \bar{C}_D force both Q and \bar{Q} HIGH.

Asynchronous Inputs:

- LOW input to \bar{S}_D sets Q to HIGH level
- LOW input to \bar{C}_D sets Q to LOW level
- Clear and Set are independent of Clock
- Simultaneous LOW on \bar{C}_D and \bar{S}_D makes both Q and \bar{Q} HIGH

Features


- Guaranteed 4000V minimum ESD protection

Ordering Code: See Section 11

Commercial	Package Number	Package Description
74F114PC	N14A	14-Lead (0.300" Wide) Molded Dual-In-Line
74F114SC (Note 1)	M14A	14-Lead (0.150" Wide) Molded Small Outline, JEDEC


Note 1: Devices also available in 13" reel. Use suffix = SCX.

Logic Symbols




TL/F/9474-3

IEEE/IEC



TL/F/9474-5

Connection Diagram



TL/F/9474-1

Unit Loading/Fan Out: See Section 2 for U.L. definitions

Pin Names	Description	74F	
		U.L. HIGH/LOW	Input I _{IH} /I _{IL} Output I _{OH} /I _{OL}
J ₁ , J ₂ , K ₁ , K ₂	Data Inputs	1.0/1.0	20 μA/ -0.6 mA
\overline{CP}	Clock Pulse Input (Active Falling Edge)	1.0/8.0	20 μA/ -4.8 mA
\overline{CD}	Direct Clear Input (Active LOW)	1.0/10.0	20 μA/ -6.0 mA
$\overline{SD}_1, \overline{SD}_2$	Direct Set Inputs (Active LOW)	1.0/5.0	20 μA/ -3.0 mA
Q ₁ , Q ₂ , \overline{Q}_1 , \overline{Q}_2	Outputs	50/33.3	-1 mA/20 mA

Truth Table

Inputs					Outputs	
\overline{SD}	\overline{CD}	CP	J	K	Q	\overline{Q}
L	H	X	X	X	H	L
H	L	X	X	X	L	H
L	L	X	X	X	H	H
H	H	↘	h	h	\overline{Q}_0	Q ₀
H	H	↘	l	h	L	H
H	H	↘	h	l	H	L
H	H	↘	l	l	Q ₀	\overline{Q}_0

H = HIGH Voltage Level

L = LOW Voltage Level


X = Immaterial

↘ = HIGH-to-LOW Clock Transition

Q₀ (\overline{Q}_0) = Before HIGH-to-LOW Transition of Clock

Lower case letters indicate the state of the referenced input or output one setup time prior to the HIGH-to-LOW clock transition.

Logic Diagram (one half shown)



TL/F/9474-4

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings (Note 1)

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	-55°C to +175°C
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0 mA
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	
Standard Output	-0.5V to V _{CC}
TRI-STATE® Output	-0.5V to +5.5V

Current Applied to Output in LOW State (Max) twice the rated I_{OL} (mA)

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	0°C to +70°C
Commercial	
Supply Voltage	
Commercial	+4.5V to +5.5V

DC Electrical Characteristics

Symbol	Parameter		74F			Units	V _{CC}	Conditions	
			Min	Typ	Max				
V _{IH}	Input HIGH Voltage		2.0			V		Recognized as a HIGH Signal	
V _{IL}	Input LOW Voltage					V		Recognized as a LOW Signal	
V _{CD}	Input Clamp Diode Voltage					V	Min	I _{IN} = -18 mA	
V _{OH}	Output HIGH Voltage	74F 10% V _{CC} 74F 5% V _{CC}	2.5 2.7			V	Min	I _{OH} = -1 mA I _{OH} = -1 mA	
V _{OL}	Output LOW Voltage	74F 10% V _{CC}			0.5	V	Min	I _{OL} = 20 mA	
I _{IH}	Input HIGH Current	74F			5.0	μA	Max	V _{IN} = 2.7V	
I _{BVI}	Input HIGH Current Breakdown Test	74F			7.0	μA	Max	V _{IN} = 7.0V	
I _{CEX}	Output High Leakage Current	74F			50	μA	Max	V _{OUT} = V _{CC}	
V _{ID}	Input Leakage Test	74F	4.75			V	0.0	I _{ID} = 1.9 μA All Other Pins Grounded	
I _{OD}	Output Leakage Circuit Current	74F			3.75	μA	0.0	V _{IOD} = 150 mV All Other Pins Grounded	
I _{IL}	Input LOW Current				-0.6 -3.0 -4.8 -6.0	mA	Max	V _{IN} = 0.5V (J _n , K _n) V _{IN} = 0.5V (S _{Dn}) V _{IN} = 0.5V (C _P) V _{IN} = 0.5V (C _{Dn})	
I _{OS}	Output Short-Circuit Current		-60			-150	mA	Max	V _{OUT} = 0V
I _{CCH}	Power Supply Current		12.0		19.0	mA	Max	V _O = HIGH	
I _{CCL}	Power Supply Current		12.0		19.0	mA	Max	V _O = LOW	

AC Electrical Characteristics: See Section 2 for Waveforms and Load Configurations

Symbol	Parameter	74F			74F		Units	Fig. No.
		T _A = +25°C V _{CC} = +5.0V C _L = 50 pF			T _A , V _{CC} = Com C _L = 50 pF			
		Min	Typ	Max	Min	Max		
f _{max}	Maximum Clock Frequency	75	95		70		MHz	2-1
t _{PLH} t _{PHL}	Propagation Delay CP to Q _n or Q̄ _n	3.0	5.0	6.5	3.0	7.5	ns	2-3
t _{PLH} t _{PHL}	Propagation Delay C̄ _{Dn} or S̄ _{Dn} to Q _n or Q̄ _n	3.0	4.5	6.5	3.0	7.5	ns	2-3

AC Operating Requirements: See Section 2 for Waveforms

Symbol	Parameter	74F		74F		Units	Fig. No.
		T _A = +25°C V _{CC} = +5.0V		T _A , V _{CC} = Com			
		Min	Max	Min	Max		
t _s (H) t _s (L)	Setup Time, HIGH or LOW J _n or K _n to C̄P	4.0		5.0		ns	2-6
		3.0		3.5			
t _h (H) t _h (L)	Hold Time, HIGH or LOW J _n or K _n to C̄P	0		0			
t _w (H) t _w (L)	C̄P Pulse Width HIGH or LOW	4.5		5.0		ns	2-4
		4.5		5.0			
t _w (L)	C̄ _{Dn} or S̄ _{Dn} Pulse Width, LOW	4.5		5.0		ns	2-4
t _{rec}	Recovery Time S̄ _{Dn} , C̄ _{Dn} , to C̄P	4.0		5.0		ns	2-6