


**FEATURES/BENEFITS**

- 5Ω bidirectional switches connect inputs to outputs
- Zero propagation delay
- Undershoot clamp diodes on all switch and control pins
- Outputs precharge voltage to minimize signal distortion during live insertion
- TTL-compatible input and output levels
- Zero ground bounce
- Available in 24-pin SOIC, QSOP and TSSOP

**DESCRIPTION**

The QS3800 is a 10-bit high-speed CMOS bus switch controlled by a single enable ( $\overline{ON}$ ) input. When  $\overline{ON}$  is LOW, the switch is on and port A is connected to port B. When  $\overline{ON}$  is HIGH, the switch between port A and port B is open and port B is precharged to the Bias voltage. The low ON resistance (5Ω) of the QS3800 allows inputs to be connected to outputs without adding propagation delay and without generating additional noise. The QS3800 also precharges the B port to a user-selectable bias voltage to minimize live-insertion noise which is useful in VME bus applications.


**Figure 1. Functional Block Diagram**



**Table 1. Pin Description**

Name	I/O	Function
A0-A9	I/O	Bus A
B0-B9	I/O	Bus B
$\overline{\text{ON}}$	I	Bus Switch Enable
$V_{\text{BIAS}}$	I	Bias Voltage

**Figure 2. Pin Configuration**  
(All Pins Top View)



**Table 2. Function Table**

$\overline{\text{ON}}$	B0-B9	Function
L	A0-A9	Connect
H	$V_{\text{BIAS}}$	Disconnect

**Table 3. Absolute Maximum Ratings**

Supply Voltage to Ground .....	-0.5V to 7.0V
Bias Voltage Range, BIAS $V$ .....	-0.5V to $V_{\text{CC}}$
DC Input Voltage $V_{\text{IN}}$ .....	-0.5V to $V_{\text{CC}} + 0.5V$
AC Input Voltage (for a pulse width $\leq 20\text{ns}$ ) .....	-3.0V
DC Output Current Max. Sink Current/Pin .....	128mA
Input Clamp Current .....	-50mA
Maximum Power Dissipation .....	0.5 watts
$T_{\text{STG}}$ Storage Temperature .....	-65° to 150°C

**Note:** ABSOLUTE MAXIMUM CONTINUOUS RATINGS are those values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute-maximum conditions is not implied.

**Table 4. Capacitance**

$T_A = 25^\circ\text{C}$ ,  $f = 1\text{MHz}$ ,  $V_{\text{IN}} = 0V$

Pins	QSOP, SOIC and TSSOP		Unit
	Typ	Max	
Control Inputs	3	5	pF
QuickSwitch Channels (Switch OFF)	5	7	pF

**Note:** Capacitance is characterized but not tested. For total capacitance while the switch is ON, please see Section 1 under "input and switch capacitance."

**Table 5. DC Electrical Characteristics Over Operating Range**


Commercial:  $T_A = -40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ ,  $V_{CC} = 5.0\text{V} \pm 10\%$

Symbol	Parameter	Test Conditions	Min	Typ <sup>(1)</sup>	Max	Unit
$V_{IH}$	Input HIGH Voltage	Guaranteed Logic HIGH for Control Inputs	2.0	—	—	V
$V_{IL}$	Input LOW Voltage	Guaranteed Logic LOW for Control Inputs	—	—	0.8	V
$V_{BIAS}$	Bias Voltage	$V_{CC} = 5\text{V}$	1.3	—	$V_{CC}$	V
$I_O$	Bias Current	$V_{CC} = 4.5\text{V}$ , $V_{BIAS} = 2.4\text{V}$ , $V_O = 0$ $ON = \text{High}$	0.25	—	—	mA
$ I_{IN} $	Input Leakage Current (Control inputs)	$0 \leq V_{IN} \leq V_{CC}$	—	—	1	$\mu\text{A}$
$ I_{OZ} $	Off-State Current (Hi-Z)	$0 \leq V_{OUT} \leq V_{CC}$	—	—	1	$\mu\text{A}$
$R_{ON}$	Switch ON Resistance <sup>(2)</sup>	$V_{CC} = \text{Min.}$ , $V_{IN} = 0.0\text{V}$ $I_{ON} = 30\text{mA}$	—	5	7	$\Omega$
$R_{ON}$	Switch ON Resistance <sup>(2)</sup>	$V_{CC} = \text{Min.}$ , $V_{IN} = 2.4\text{V}$ $I_{ON} = 15\text{mA}$	—	10	15	$\Omega$

**Notes:**

1. Typical values indicate  $V_{CC} = 5.0\text{V}$  and  $T_A = 25^{\circ}\text{C}$ .
2. For a diagram explaining the procedure for  $R_{ON}$  measurement, please see Section 1 under "DC Electrical Characteristics."
3. Max. value of  $R_{ON}$  guaranteed by characterization, but not production tested.

**Figure 3. Typical ON Resistance vs  $V_{IN}$  at  $V_{CC} = 5.0\text{V}$**



**Table 6. Power Supply Characteristics Over Operating Range**

$T_A = -40^\circ\text{C}$  to  $85^\circ\text{C}$ ,  $V_{CC} = 5.0\text{V} \pm 10\%$

Symbol	Parameter	Test Conditions <sup>(1)</sup>	Typ <sup>(2)</sup>	Max	Unit
$I_{CCQ}$	Quiescent Power Supply Current	$V_{CC} = \text{Max.}, V_{IN} = \text{GND}$ or $V_{CC}, f = 0$	0.2	3.0	$\mu\text{A}$
$\Delta I_{CC}$	Power Supply Current per Input HIGH	$V_{CC} = \text{Max.}, V_{IN} = 3.4\text{V}^{(3)}, f = 0$ per Control Input	—	2.5	mA
$Q_{CCD}$	Dynamic Power Supply Current per MHz <sup>(4)</sup>	$V_{CC} = \text{Max.}, A$ and $B$ Pins Open, Data Inputs = GND, Control Inputs Toggling @ 50% Duty Cycle	—	0.25	mA/MHz

**Notes:**

1. For conditions shown as Min. or Max., use the appropriate values specified under DC specifications.
2. Typical Values are at  $V_{CC} = 5.0\text{V}$ ,  $25^\circ\text{C}$  Ambient.
3. Per TTL driven input ( $V_{IN} = 3.4\text{V}$ , control inputs only). A and B pins do not contribute to  $\Delta I_{CC}$ .
4. This current applies to the control inputs only and represents the current required to switch internal capacitance at the specified frequency. The A and B inputs generate no significant AC or DC currents as they transition. This parameter is guaranteed by design, but not tested.

**Table 7. Switching Characteristics Over Operating Range**

Commercial:  $T_A = -40^\circ\text{C}$  to  $85^\circ\text{C}$ ,  $V_{CC} = 5.0\text{V} \pm 10\%$

$C_{LOAD} = 50\text{pF}$ ,  $R_{LOAD} = 500\Omega$  unless otherwise noted

Symbol	Description <sup>(1)</sup>	Test Conditions	Min	Typ	Max	Unit
$t_{PLH}$ $t_{PHL}$	Data Propagation Delay <sup>(2,3)</sup> A to B or B to A		—	0.25 <sup>(3)</sup>	—	ns
$t_{PZL}$ $t_{PZH}$	Switch Turn-on Delay $\overline{\text{ON}}$ to A or B	$V_{BIAS} = 3\text{V}$ , $V_{BIAS} = \text{GND}$	1.5	—	7.5	ns
$t_{PLZ}$ $t_{PHZ}$	Switch Turn-off Delay <sup>(2)</sup> $\overline{\text{ON}}$ to A or B	$V_{BIAS} = 3\text{V}$ , $V_{BAIS} = \text{GND}$	1.5	—	6.5	ns

**Notes:**

1. See Test Circuit and Waveforms. Minimums guaranteed but not tested.
2. This parameter is guaranteed by design but not tested.
3. The bus switch contributes no propagation delay other than the RC delay of the ON resistance of the switch and the load capacitance. The time constant for the switch alone is of the order of 0.25ns for 50pF. Since this time constant is much smaller than the rise/fall times of typical driving signals, it adds very little propagation delay to the system. Propagation delay of the bus switch when used in a system is determined by the driving circuit on the driving side of the switch and its interaction with the load on the driven side.