

# SN54F573, SN74F573 OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS

D3034, JULY 1987—REVISED JANUARY 1989

- 8 Latches in a Single Package
- 3-State Bus-Driving True Outputs
- Full Parallel Access for Loading
- Buffered Control Inputs
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

## description

These 8-bit latches feature three-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.


The eight latches of the 'F573 are transparent D-type latches. While the enable (C) is high, the Q outputs will follow the data (D) inputs. When the enable is taken low, the Q outputs will be latched at the levels that were set up at the D inputs.

A buffered output-control input ( $\overline{OC}$ ) can be used to place the eight outputs in either a normal logic state (high or low logic levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance third state and increased drive provide the capability to drive the bus lines in a bus-organized system without need for interface or pull-up components.


The output control  $\overline{OC}$  does not affect the internal operations of the latches. Old data can be retained, or new data can be entered while the outputs are off.

The SN54F573 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74F573 is characterized for operation from  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ .

SN54F573 . . . J PACKAGE  
SN74F573 . . . DW OR N PACKAGE  
(TOP VIEW)



SN54F573 . . . FK PACKAGE  
(TOP VIEW)




FUNCTION TABLE (EACH LATCH)

INPUTS				OUTPUT
$\overline{OC}$	ENABLE	C	D	Q
L	H	H	H	H
L	H	L	L	L
L	L	X	X	$Q_0$
H	X	X	X	Z


# SN54F573, SN74F573 OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS

logic symbol†



†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagram (positive logic)



2

Data Sheets

# SN54F573, SN74F573

## OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS

### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, $V_{CC}$ .....	-0.5 V to 7 V
Input voltage <sup>†</sup> .....	-1.2 V to 7 V
Input current .....	-30 mA to 5 mA
Voltage applied to any output in the disabled or power-off state .....	-0.5 V to 5.5 V
Voltage applied to any output in the high state .....	-0.5 V to $V_{CC}$
Current into any output in the low state: SN54F573 .....	40 mA
SN74F573 .....	48 mA
Operating free-air temperature range: SN54F573 .....	-55°C to 125°C
SN74F573 .....	0°C to 70°C
Storage temperature range .....	-65°C to 150°C

<sup>†</sup>The input voltage ratings may be exceeded provided the input current ratings are observed.

### recommended operating conditions

		SN54F573			SN74F573			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
$V_{CC}$	Supply voltage	4.5	5	5.5	4.75	5	5.25	V
$V_{IH}$	High-level input voltage	2			2			V
$V_{IL}$	Low-level input voltage			0.8			0.8	V
$I_{IK}$	Input clamp current			-18			-18	mA
$I_{OH}$	High-level output current			-3			-3	mA
$I_{OL}$	Low-level output current			20			24	mA
$T_A$	Operating free-air temperature	-55	125		0	70		°C

### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS		SN54F573			SN74F573			UNIT
			MIN	TYP <sup>‡</sup>	MAX	MIN	TYP <sup>‡</sup>	MAX	
$V_{IK}$	$V_{CC} = 4.5$ V,	$I_I = -18$ mA			-1.2			-1.2	V
$V_{OH}$	$V_{CC} = 4.5$ V	$I_{OH} = -1$ mA	2.5	3.4		2.5	3.4		V
		$I_{OH} = -3$ mA	2.4	3.3		2.4	3.3		
$V_{OL}$	$V_{CC} = 4.75$ V,	$I_{OH} = -1$ to $-3$ mA				2.7			V
		$V_{CC} = 4.5$ V	$I_{OL} = 20$ mA	0.30	0.5				
		$I_{OL} = 24$ mA				0.35	0.5		
$I_{OZH}$	$V_{CC} = 5.5$ V,	$V_O = 2.7$ V			50			50	μA
$I_{OZL}$	$V_{CC} = 5.5$ V,	$V_O = 0.5$ V			-50			-50	μA
$I_I$	$V_{CC} = 5.5$ V,	$V_I = 7$ V			0.1			0.1	mA
$I_{IH}$	$V_{CC} = 5.5$ V,	$V_I = 2.7$ V			20			20	μA
$I_{IL}$	$V_{CC} = 5.5$ V,	$V_I = 0.5$ V			-0.6			-0.6	mA
$I_{OS}^{\S}$	$V_{CC} = 5.5$ V,	$V_O = 0$	-60		-150	-60		-150	mA
$I_{CCZ}$	$V_{CC} = 5.5$ V,	See Note 1	38	55		38	55		mA

<sup>‡</sup>All typical values are at  $V_{CC} = 5$  V,  $T_A = 25$ °C.

<sup>\S</sup>Not more than one output should be shorted at a time, and the duration of the short circuit should not exceed 1 second.

NOTE 1:  $I_{CCZ}$  is measured with  $\overline{OC}$  at 4.5 V and all other inputs grounded.

2

Data Sheets

# SN54F573, SN74F573 OCTAL D-TYPE TRANSPARENT LATCHES WITH 3-STATE OUTPUTS

## timing requirements

		V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25°C		V <sub>CC</sub> = 4.5 V to 5.5 V, T <sub>A</sub> = MIN to MAX†				UNIT	
		'F573			SN54F573		SN74F573		
		MIN	MAX	MIN	MAX	MIN	MAX		
t <sub>SU</sub>	Setup time, Data before Enable C↓	2				2		ns	
t <sub>H</sub>	Hold time, Data before Enable C↓	3				3		ns	
t <sub>W</sub>	Pulse duration, Enable C high	6				6		ns	

## switching characteristics (see Note 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V <sub>CC</sub> = 5 V, C <sub>L</sub> = 50 pF, R1 = 500 Ω, R2 = 500 Ω, T <sub>A</sub> = 25°C			V <sub>CC</sub> = 4.5 V to 5.5 V, C <sub>L</sub> = 50 pF, R1 = 500 Ω, R2 = 500 Ω, T <sub>A</sub> = MIN to MAX†				UNIT
			'F573			SN54F573		SN74F573		
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
			t <sub>PLH</sub>	D	Q	2	4.9	7		
t <sub>PHL</sub>	1.2	3.3	5					1.2	6	
t <sub>PLH</sub>	C	Q	4.2	8.6	11.5			4.2	13	ns
t <sub>PHL</sub>			2.2	4.8	7			2.2	8	
t <sub>PZH</sub>	OC	Q	1.2	4.6	11			1.2	12	ns
t <sub>PZL</sub>			1.2	5.2	7.5			1.2	8.5	
t <sub>PHZ</sub>	OC	Q	1.2	4.1	6.5			1.2	7.5	ns
t <sub>PLZ</sub>			1.2	3.4	6			1.2	6	

†For conditions shown as MIN or MAX, use the appropriate value specified under Recommended Operating Conditions.

NOTE 2: Load circuits and waveforms are shown in Section 1.