

Features

- Low On-Resistance (33Ω typ) Minimizes Distortion and Error Voltages
- Low Glitching Reduces Step Errors in Sample-and-Holds. Charge Injection, 2pC typ
- Single-Supply Operation (+2.5V to +16V)
- Improved Second Sources for MAX323/MAX324/MAX325
- On-Resistance Matching Between Channels, <math><2\Omega</math>
- On-Resistance Flatness, <math><6\Omega</math> max
- Low Off-Channel Leakage, <math><5\text{nA}</math> @ +85°C
- TTL/CMOS Logic Compatible
- Fast Switching Speed, $t_{\text{ON}} < 150\text{ns}</math>$
- Guaranteed Break-Before-Make action (PS325 only) eliminates momentary crosstalk
- Rail-to-Rail Analog Signal Dynamic Range
- Low Power Consumption, <math><5\mu\text{W}</math>
- MSOP Package Minimizes Board Area

Applications

- Audio Switching and Routing
- Portable Instruments
- Data Acquisition Systems
- Sample-and-Holds
- Telecommunication Systems
- Battery-Powered Systems


Description

The PS323/PS324/PS325 are improved high-precision, medium-voltage analog switches designed to operate with single power supplies. The PS323 is a dual, single-pole single-throw (SPST), normally open (NO) switch. The PS324 has the same pinout as the PS323 but it has two normally closed (NC) switches. The PS325 has one normally open (NO) and one normally closed (NC) switch per package. Each switch conducts current equally well in either direction when on. In the off state, each switch blocks voltages up to the power-supply rail.

With a +5V power supply, the PS323/PS324/PS325 guarantee <math><60\Omega</math> ON-resistance. ON-resistance matching between channels is within 2Ω. ON-resistance flatness is less than 6Ω over the specified range. All three devices guarantee low leakage currents (<math><100\text{pA}</math> @ 25°C, <math><10\text{nA}</math> @ +85°C) and fast switching speeds ($t_{\text{ON}} < 150\text{ns}</math>). Break-before-make switching action protects against momentary crosstalk (PS325).$


For single-supply operation below 5V, PI5A317/318/319 are also recommended.

Functional Diagrams, Pin Configurations, and Truth Tables



Top View


PS323	
Logic	Switch
0	OFF
1	ON



Top View

Switches shown for logic "0" input

PS324	
Logic	Switch
0	ON
1	OFF



Top View

PS325		
Logic	Switch 1	Switch 2
0	OFF	ON
1	ON	OFF

For free samples and the latest literature: www.pericom.com, or phone 1-800-435-2336

Absolute Maximum Ratings

Voltages Referenced to GND

V+ -0.3V to +17V

V_{IN}, V_{COM}, V_{NC}, V_{NO} ⁽¹⁾ -2V to (V+) +2V
or 30mA, whichever occurs first

Current (any terminal) 30mA

Peak Current, COM, NO, NC

(pulsed at 1ms, 10% duty cycle) 100mA

ESD per Method 3015.7 >2000V

Thermal Information

Continuous Power Dissipation

Plastic DIP (derate 6mW/°C above +70°C) 500mW

Narrow SO (derate 6mW/°C above +70°C) 450mW

MSOP (derate 4mW/°C above +70°C) 330mW

Storage Temperature -65°C to +150°C

Lead Temperature (soldering, 10s) +300°C

Note 1: Signals on NC, NO, COM, or IN exceeding V+ or GND are clamped by internal diodes. Limit forward diode current to 30mA maximum.

Caution: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied.

Electrical Specifications - Single +5V Supply

(V+ = 5V +10%, GND = 0V, V_{INH} = 2.4V, V_{INL} = 0.8V)

Parameter	Symbol	Conditions	Temp. (°C)	Min ⁽²⁾	Typ ⁽¹⁾	Max ⁽²⁾	Units
Analog Switch							
Analog Signal Range ⁽³⁾	V _{ANALOG}		Full	0		V+	V
On Resistance	R _{ON}	V+ = 4.5V, V _{NO} or V _{NC} = +3.5V I _{COM} = 1mA	25		33	60	Ω
			Full			75	
On-Resistance Match Between Channels ⁽⁴⁾	ΔR _{ON}	V _{NO} or V _{NC} = +3V, I _{COM} = 1mA, V+ = 5V	25		0.8	2	
			Full			4	
On-Resistance Flatness ⁽⁵⁾	R _{FLAT(ON)}	V+ = 5V, I _{COM} = 1mA, V _{NO} or V _{NC} = 1V, 2V, 3V,	25		2	6	
			Full			8	
NO or NC Off Leakage Current ⁽⁶⁾	I _{NO(OFF)} or I _{NC(OFF)}	V+ = 5.5V, V _{COM} = 1V, V _{NO} or V _{NC} = 4.5V	25	-0.1	-0.01	0.1	nA
			Full	-5		5	
COM Off Leakage Current ⁽⁶⁾	I _{COM(OFF)}	V+ = 5.5V, V _{COM} = 4.5V, V _{NO} or V _{NC} = 1V	25	-0.1	-0.01	0.1	
			Full	-5		5	
COM On Leakage Current ⁽⁶⁾	I _{COM(ON)}	V+ = 5.5V, V _{COM} = 5V, V _{NO} or V _{NC} = 5V	25	-0.2	-0.04	0.2	
			Full	-10		10	

Electrical Specifications - Single +5V Supply (continued)

(V₊ = 5V ±10%, GND = 0V, V_{INH} = 2.4V, V_{INL} = 0.8V)

Parameter	Symbol	Conditions	Temp. (°C)	Min ⁽¹⁾	Typ ⁽²⁾	Max ⁽¹⁾	Units	
Logic Input								
Input Current with Input Voltage High	I _{INH}	V _{IN} = 2.4V, all others = 0.8V	Full	-0.5	0.005	0.5	μA	
Input Current with Input Voltage Low	I _{INL}	V _{IN} = 0.8V, all others = 2.4V		-0.5	0.005	0.5		
Logic High Input Voltage	V _{INH}			2.4			V	
Logic Low Input Voltage	V _{INL}					0.8		
Dynamic								
Turn-On Time	t _{ON}	V _{NO} OR V _{NC} = 3V, Figure 2	25		85	150	ns	
			Full					240
Turn-Off Time	t _{OFF}		25		25	100		
			Full			150		
Break-Before-Make Time Delay ⁽³⁾	t _D	PS325 only, R _L = 300Ω, C _L = 35pF, Figure 3	25	2	5		pC	
Charge Injection ⁽³⁾	Q	C _L = 1nF, V _{GEN} = 0V, R _{GEN} = 0Ω, Figure 4				1		5
Off Isolation ⁽⁷⁾	OIRR	R _L = 50Ω, C _L = 5pF, f = 1MHz, Figure 5				-72		
Crosstalk	X _{TALK}	R _L = 50Ω, C _L = 5pF, f = 1MHz, Figure 6				-85		
NC or NO Off Capacitance	C _(OFF)	f = 1MHz, Figure 7				9		pF
COM Off Capacitance	C _{COM(OFF)}					9		
COM On Capacitance	C _{COM(ON)}			f = 1MHz, Figure 8			22	
Supply								
Power-Supply Range	V ₊		Full	2.7		16	V	
Positive Supply Current	I ₊	V ₊ = 5.5V, V _{IN} = 0V or V ₊ , all channels on or off			-1		1	μA

Notes:

1. The algebraic convention, where the most negative value is a minimum and the most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design
4. ΔR_{ON} = R_{ON} max - R_{ON} min
5. Flatness is defined as the difference between the maximum and minimum value of ON-resistance measured.
6. Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
7. Off Isolation = 20log₁₀ [V_{COM} / (V_{NC} OR V_{NO})]. See Figure 5.

Electrical Specifications - Single +3.3V Supply

($V_+ = 3.3V \pm 10\%$, $GND = 0V$, $V_{INH} = 2.4V$, $V_{INL} = 0.8V$)

Parameter	Symbol	Conditions	Temp (°C)	Min ⁽¹⁾	Typ ⁽²⁾	Max ⁽¹⁾	Units
Analog Switch							
Analog Signal Range ⁽³⁾	V_{ANALOG}			0		V_+	V
On-Resistance	R_{ON}	$V_+ = 3V$, $I_{COM} = 1mA$, V_{NO} or $V_{NC} = 1.5V$	25		83	175	Ω
			Full			275	
Dynamic							
Turn-On Time ⁽³⁾	t_{ON}	V_{NO} or $V_{NC} = 1.5V$, Figure 2	25		160	400	ns
			Full			500	
Turn-Off Time ⁽³⁾	t_{OFF}		25		40	125	
			Full			175	
Break-Before-Make Time Delay ⁽³⁾	t_D	PS325 only	25	2	5		
Charge Injection ⁽³⁾	Q	$C_L = 1nF$, $V_{GEN} = 0V$, $R_{GEN} = 0\Omega$, Figure 4	25		1	5	pC
Supply							
Positive Supply Current	I_+	$V_+ = 3.6V$, $V_{IN} = 0V$ or V_+ , all channels on or off	Full	-1	0.01	1	μA

Test Circuits/Timing Diagrams




Figure 2. Switching Time




Figure 3. Break-Before-Make Interval (PS325 only)




Figure 4. Charge Injection

Test Circuits/Timing Diagrams (continued)




Figure 5. Off Isolation




Figure 6. Crosstalk




Figure 7. Channel-Off Capacitance




Figure 8. Channel-On Capacitance

Ordering Information

Part	Temp. Range	Package
PS323CPA	0°C to +70°C	8 Plastic DIP
PS323CSA	0°C to +70°C	8 Narrow SO
PS323CUA	0°C to +70°C	8 MSOP
PS323EPA	-40°C to +85°C	8 Plastic DIP
PS323ESA	-40°C to +85°C	8 Narrow SO
PS323EUA	-40°C to +85°C	8 MSOP
PS324CPA	0°C to +70°C	8 Plastic DIP
PS324CSA	0°C to +70°C	8 Narrow SO
PS324CUA	0°C to +70°C	8 MSOP

Part	Temp. Range	Package
PS324EPA	-40°C to +85°C	8 Plastic DIP
PS324ESA	-40°C to +85°C	8 Narrow SO
PS324EUA	-40°C to +85°C	8 MSOP
PS325CPA	0°C to +70°C	8 Plastic DIP
PS325CSA	0°C to +70°C	8 Narrow SO
PS325CUA	0°C to +70°C	8 MSOP
PS325EPA	-40°C to +85°C	8 Plastic DIP
PS325ESA	-40°C to +85°C	8 Narrow SO
PS325EUA	-40°C to +85°C	8 MSOP