

Recommended Operating Conditions

SYMBOL	PARAMETER		MIN	NOM	MAX	UNIT
V _{CC}	Supply voltage	54	4.5	5	5.5	V
		74	4.75	5	5.25	
I _{OH}	High-level output current	54, 74			-400	μA
I _{OL}	Low-level output current	54			4	mA
		74			8	
T _A	Operating free-air temperature	54	-55		125	°C
		74	0		70	

Electrical Characteristics over recommended operating free-air temperature range (unless otherwise noted)

SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP (Note 1)	MAX	UNIT	
V _{IH}	High-level input voltage			2		V	
V _{IL}	Low-level input voltage		54		0.7	V	
			74		0.8		
V _{IK}	Input clamp voltage	V _{CC} = Min, I _I = -18mA			-1.5	V	
V _{OH}	High-level output voltage	V _{CC} = Min, V _{IH} = Min, I _{OH} = Max	54	2.5	3.4	V	
			74	2.7	3.4		
V _{OL}	Low-level output voltage	V _{CC} = Min, I _{OL} = 4mA	54, 74	0.25	0.4	V	
		V _{IL} = Max, I _{OL} = 8mA	74	0.35	0.5		
I _I	Input current at maximum input voltage	V _{CC} = Max, V _I = 7V			0.1	mA	
I _{IH}	High-level input current	V _{CC} = Max, V _I = 2.7V			20	μA	
I _{IL}	Low-level input current	V _{CC} = Max, V _I = 0.4V			-0.4	mA	
I _{OS}	Short-circuit output current	V _{CC} = Max (Note 2)			-20	-100	mA
I _{CC}	Supply current	Total with outputs high V _{CC} = Max			2.4	4.8	mA
I _{CL}		Total with outputs low V _{CC} = Max			4.4	8.8	mA

Note 1: All typical values are at V_{CC} = 5V, T_A = 25°C

Note 2: Not more than one output should be shorted at a time, and duration should not exceed one second.

Switching Characteristics, V_{CC} = 5V, T_A = 25°C

SYMBOL	PARAMETER	TEST CONDITION#	MIN	TYP	MAX	UNIT
t _{PLH}	Propagation delay time, low-to-high-level output	C _L = 15pF, R _L = 2kΩ		8	15	ns
t _{PHL}	Propagation delay time, high-to-low-level output			10	20	

#For load circuit and voltage wave forms, see page 3-11.