

DM74ALS240A/DM74ALS241A/74ALS240A-1/ DM64ALS240A Octal TRI-STATE® Bus Driver


General Description

These octal TRI-STATE bus drivers are designed to provide the designer with flexibility in implementing a bus interface with memory, microprocessor, or communication systems. The output TRI-STATE gating control is organized into two separate groups of four buffers. The 'ALS240A control inputs symmetrically enable the respective outputs when set logic low, while the 'ALS241A has complementary enable gating. The TRI-STATE circuitry contains a feature that maintains the buffer outputs in TRI-STATE (high impedance state) during power supply ramp-up or ramp-down. This eliminates bus glitching problems that arise during power-up and power-down.

The 'ALS240-1 version features the same performance as the standard version with the addition of increased current drive capability to meet the current requirements of various bus architectures. For all ALS-1 products, the recommended maximum I_{OL} is increased to 48 mA.

The DM64ALS240A version features the same performance as the standard version DM74ALS240A with a guarantee over an extended temperature range (-40°C to +85°C).


Connection Diagrams



Top View

Order Number DM64ALS240AWM, DM64ALS240AN,
DM74ALS240AWM, DM74ALS240AN, DM74ALS240ASJ,
74ALS240A-1N or 74ALS240A-1WM

See NS Package Number M20B, M20D or N20A



Top View

Order Number DM74ALS241AWM or DM74ALS241AN
See NS Package Number M20B or N20A

Features

- Maximum I_{OL} increased to 48 mA for 'ALS240A-1 product
- Advanced low power oxide-isolated ion-implanted Schottky TTL process
- Functional and pin compatible with the DM54/74LS counterpart
- Improved switching performance with less power dissipation compared with the DM54/74LS counterpart
- Switching response specified into 500Ω and 50 pF load
- Switching response specifications guaranteed over full temperature and V_{CC} supply range
- PNP input design reduces input loading
- Low level drive current:
74ALS = 24 mA
- DM64ALS240A guarantee over extended temperature
-40°C to +85°C

Function Tables

'ALS240A, 'ALS240A-1

Input		Output Y
\bar{G}	A	
L	L	H
L	H	L
H	X	Z

'ALS241A

Input		Output Y
2G	2A	
H	L	L
H	H	H
L	X	Z

'ALS241A

Input		Output Y
$\bar{1G}$	1A	
L	L	L
L	H	H
H	X	Z

H = High Level Logic State

L = Low Level Logic State

X = Don't Care (Either Low or High Level Logic State)

Z = High Impedance (Off) State

Absolute Maximum Ratings

Supply Voltage, V _{CC}	7V	Typical θ_{JA}	60.5°C/W
Input Voltage	7V	N Package	79.8°C/W
Voltage Applied to Disabled Output	5.5V	M Package	
Operating Free Air Temperature Range			
DM74ALS	0°C to +70°C		
DM64ALS	-40°C to +85°C		
Storage Temperature Range	-65°C to +150°C		

Note: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Recommended Operating Conditions

Symbol	Parameter	DM74ALS240A, 240A-1, 241A, DM64ALS240A			Units
		Min	Typ	Max	
V _{CC}	Supply Voltage	4.5	5	5.5	V
V _{IH}	High Level Input Voltage	2			V
V _{IL}	Low Level Input Voltage			0.8	V
I _{OH}	High Level Output Current			-15	mA
I _{OL}	Low Level Output Current	'ALS240A, 'ALS241A		24	mA
		'ALS240A-1		48	
T _A	Operating Free Air Temperature	0		70	°C

Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise specified)

Symbol	Parameter	Conditions	DM74ALS240A, 240A-1, 241A, DM64ALS240A			Units
			Min	Typ	Max	
V _{IK}	Input Clamp Voltage	V _{CC} = 4.5V, I _I = -18 mA			-1.5	V
V _{OH}	High Level Output Voltage	V _{CC} = 4.5V to 5.5V	I _{OH} = -0.4 mA	V _{CC} - 2		V
		V _{CC} = 4.5V	I _{OH} = -3 mA	2.4		V
			I _{OH} = Max	2		V
V _{OL}	Low Level Output Voltage	V _{CC} = 4.5V I _{OL} = Max		0.35	0.5	V
I _I	Input Current at Max Input Voltage	V _{CC} = 5.5V, V _I = 7V			0.1	mA
I _{IH}	High Level Input Current	V _{CC} = 5.5V, V _I = 2.7V			20	μA
I _{IL}	Low Level Input Current	V _{CC} = 5.5V, V _{IL} = 0.4V			-0.1	mA
I _O	Output Drive Current	V _{CC} = 5.5V, V _O = 2.25V	-30		-112	mA
I _{OZH}	High Level TRI-STATE Output Current	V _{CC} = 5.5V, V _O = 2.7V			20	μA
I _{OZL}	Low Level TRI-STATE Output Current	V _{CC} = 5.5V, V _O = 0.4V			-20	μA
I _{CC}	Supply Current	V _{CC} = 5.5V, ALS240A, ALS240A-1 Outputs High		4	10	mA
		Outputs Low		13	23	mA
		Outputs TRI-STATE		14	25	mA
		V _{CC} = 5.5V, ALS241A Outputs High		9	15	mA
		Outputs Low		15	26	mA
		Outputs TRI-STATE		17	30	mA

'ALS240A and 240A-1 Switching Characteristics

over recommended operating free air temperature range (Note 1)



Symbol	Parameter	Conditions	From (Input)	To (Output)	DM64ALS240A, DM74ALS240A, 74ALS240A-1		Units
					Min	Max	
t _{PLH}	Propagation Delay Time Low to High Level Output	V _{CC} = 4.5V to 5.5V, C _L = 50 pF, R ₁ = 500Ω, R ₂ = 500Ω, T _A = Min to Max	A	Y	2	9	ns
t _{PHL}	Propagation Delay Time High to Low Level Output				2	9	ns
t _{PZH}	Output Enable Time to High Level Output		G̅	Y	3	13	ns
t _{PZL}	Output Enable Time to Low Level Output				3	18	ns
t _{PHZ}	Output Disable Time from High Level Output		G̅	Y	2	10	ns
t _{PLZ}	Output Disable Time from Low Level Output				3	12	ns

'ALS241A Switching Characteristics



over recommended operating free air temperature range (Note 1)

Symbol	Parameter	Conditions	From (Input)	To (Output)	DM74ALS241A		Units
					Min	Max	
t _{PLH}	Propagation Delay Time Low to High Level Output	V _{CC} = 4.5V to 5.5V, C _L = 50 pF, R ₁ = 500Ω, R ₂ = 500Ω, T _A = Min to Max	A	Y	3	11	ns
t _{PHL}	Propagation Delay Time High to Low Level Output				3	10	ns
t _{PZH}	Output Enable Time to High Level Output		1G̅	Y	3	21	ns
t _{PZL}	Output Enable Time to Low Level Output				3	21	ns
t _{PHZ}	Output Disable Time to High Level Output		1G̅	Y	2	10	ns
t _{PLZ}	Output Disable Time to Low Level Output				3	15	ns
t _{PZH}	Output Enable Time to High Level Output		2G	Y	7	21	ns
t _{PZL}	Output Enable Time to Low Level Output				7	21	ns
t _{PHZ}	Output Disable Time from High Level Output		2G	Y	2	10	ns
t _{PLZ}	Output Disable Time from Low Level Output				3	15	ns

Note 1: See Section 5 for test waveforms and output load.

Logic Diagrams**ALS240A, ALS240A-1**

TL/F/6210-3

ALS241A

TL/F/6210-4