

54ACTQ32QML

54ACTQ32QML Quiet Series Quad 2-Input OR Gate



Literature Number: SNOSAM1

54ACTQ32QML

Quiet Series Quad 2-Input OR Gate

General Description

The 'ACTQ32 contains four, 2-input OR gates and utilizes NSC Quiet Series technology to guarantee quiet output switching and improved dynamic threshold performance. FACT Quiet Series™ features GTO™ output control and undershoot corrector in addition to a split ground bus for superior ACMOS performance.


Features

- Radiation features 54ACTQ32 guaranteed to 100k rd(Si)
- I_{CC} reduced by 50%
- Minimum 4KV ESD protection
- Guaranteed simultaneous switching noise level and dynamic threshold performance
- Improved latch-up immunity
- Outputs source/sink 24 mA
- ACTQ32 has TTL-compatible inputs

Ordering Information

NS Part Number	JAN Part Number	NS Package Number	Package Description
54ACTQ32JRQMLV	5962R8973601VCA 100k rd(Si)	J14A	14LD CERDIP
54ACTQ32WRQMLV	5962R8973601VDA 100k rd(Si)	W14B	14LD CERPACK


Logic Symbol



GTO™ is a trademark of National Semiconductor Corporation.
FACT™ and FACT Quiet Series™ are trademarks of Fairchild Semiconductor Corporation.

Connection Diagram

Pin Assignment for DIP and Flatpak



20139403

Pin Names	Description
A_n, B_n	Inputs
O_n	Outputs

Capacitance

Symbol	Parameter	Max	Units	Conditions
C_I	Input Capacitance	10.0	pF	$V_{CC} = \text{Open}$
C_{PD}	Power Dissipation Capacitance	72.0	pF	$V_{CC} = 5.0V$

Absolute Maximum Ratings (Note 1)

Supply Voltage (V_{CC})	-0.5V to +7.0V
DC Input Diode Current (I_{IK})	
$V_I = -0.5V$	-20 mA
$V_I = V_{CC} + 0.5V$	+20 mA
DC Input Voltage (V_I)	-0.5V to $V_{CC} + 0.5V$
DC Output Diode Current (I_{OK})	
$V_O = -0.5V$	-20 mA
$V_O = V_{CC} + 0.5V$	+20 mA
DC Output Voltage (V_O)	-0.5V to $V_{CC} + 0.5V$
DC Output Source or Sink Current (I_O)	±50 mA
DC V_{CC} or Ground Current per Output Pin (I_{CC} or I_{Gnd})	±50 mA
Thermal Resistance, Junction to Case (θ_{JC})	See Mil-Std-1835
Storage Temperature (T_{Stg})	-65°C ≤ T_A ≤ +150°C
Junction Temperature (T_J)	175°C
Maximum Power Dissipation (P_D)	500mW
Lead Temperature (soldering, 10 seconds)	300°C

Recommended Operating Conditions

Supply Voltage (V_{CC})	4.5V to 5.5V
Input Voltage (V_I)	0V to V_{CC}
Output Voltage (V_O)	0V to V_{CC}
Operating Temperature (T_A)	-55°C ≤ T_A ≤ +125°C
Minimum Input Edge Rate ($\Delta V/\Delta t$)	125 mV/ns
V_I from 0.8V to 2.0V	
V_{CC} @ 4.5V, 5.5V	
Maximum High Level Output Current (I_{OH})	-24mA
Maximum Low Level Output Current (I_{OL})	+24mA

Radiation Features

54ACTQ32JRQMLV	100 krad (Si)
54ACTQ32WRQMLV	100 krad (Si)

Quality Conformance Inspection

Mil-Std-883, Method 5005 - Group A

Subgroup	Description	Temp °C
1	Static tests at	25
2	Static tests at	125
3	Static tests at	-55
4	Dynamic tests at	25
5	Dynamic tests at	125
6	Dynamic tests at	-55
7	Functional tests at	25
8A	Functional tests at	125
8B	Functional tests at	-55
9	Switching tests at	25
10	Switching tests at	125
11	Switching tests at	-55

54ACTQ32–QMLV RH Electrical Characteristics

DC Parameters

The following conditions apply, unless otherwise specified.

DC: $V_{CC} = 4.5V$ to $5.5V$, Temperature range $-55^{\circ}C$ to $125^{\circ}C$

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub-groups	
I_{IH}	High Level Input Current	$V_{CC} = 5.5V, V_{IH} = 5.5V$	(Note 2), (Note 3)		0.1	μA	1	
			(Note 2), (Note 3)		1.0	μA	2, 3	
I_{IL}	Low Level Input Current	$V_{CC} = 5.5V, V_{IL} = 0.0V$	(Note 2), (Note 3)		-0.1	μA	1	
			(Note 2), (Note 3)		-1.0	μA	2, 3	
V_{OL}	Low Level Output Voltage	$V_{CC} = 4.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = 50.0\mu A$	(Note 2), (Note 3)		0.1	V	1, 2, 3	
			(Note 2), (Note 3)		0.1	V	1, 2, 3	
		$V_{CC} = 4.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = 24.0mA$	(Note 2), (Note 3)		0.36	V	1	
			(Note 2), (Note 3)		0.5	V	2, 3	
		$V_{CC} = 5.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = 24.0mA$	(Note 2), (Note 3)		0.36	V	1	
			(Note 2), (Note 3)		0.5	V	2, 3	
V_{IOL}	Dynamic Output Current LOW	$V_{CC} = 5.5V, V_{IH} = 5.5V,$ $V_{IL} = 0.0V, I_{OL} = 50.0mA$	(Note 2), (Note 3), (Note 6)		1.65	V	1, 2, 3	
V_{OH}	High Level Output Voltage	$V_{CC} = 4.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = -50.0\mu A$	(Note 2), (Note 3)	4.40		V	1, 2, 3	
			(Note 2), (Note 3)		5.40		V	1, 2, 3
		$V_{CC} = 4.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = -24.0mA$	(Note 2), (Note 3)		3.86		V	1
			(Note 2), (Note 3)		3.70		V	2, 3
		$V_{CC} = 5.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = -24.0mA$	(Note 2), (Note 3)		4.86		V	1
			(Note 2), (Note 3)		4.70		V	2, 3
V_{IOH}	Dynamic Output Current HIGH	$V_{CC} = 5.5V, V_{IH} = 2.0V,$ $V_{IL} = 0.8V, I_{OL} = -50.0mA$	(Note 2), (Note 3), (Note 6)	3.85		V	1, 2, 3	
I_{CCH}	Supply Current	$V_{CC} = 5.5V, V_{IH} = 5.5V$	(Note 2), (Note 3)		100	nA	1	
			(Note 2), (Note 3)		40	μA	2, 3	
I_{CCL}	Supply Current	$V_{CC} = 5.5V, V_{IH} = 0.0V$	(Note 2), (Note 3)		100	nA	1	
			(Note 2), (Note 3)		40	μA	2, 3	

54ACTQ32–QMLV RH Electrical Characteristics (Continued)**DC Parameters** (Continued)

The following conditions apply, unless otherwise specified.

DC: $V_{CC} = 4.5V$ to $5.5V$, Temperature range $-55^{\circ}C$ to $125^{\circ}C$

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub-groups
I_{CCF}	Supply Current Functional	$V_{CC} = 5.5V, V_{IH} = 0.0V$	(Note 2), (Note 3)		100	nA	1
			(Note 2), (Note 3)		40	μA	2, 3
I_{CCT}	Supply Current	$V_{CC} = 5.5V, V_{IH} = 3.4V$	(Note 2), (Note 3)		1.0	mA	1
			(Note 2), (Note 3)		1.6	mA	2, 3
V_{IKL}		$V_{CC} = 4.5V, I_{KL} = -18mA$	(Note 2), (Note 3)		-1.2	V	1, 2, 3
V_{IKH}		$V_{CC} = 4.5V, I_{KH} = 18mA$	(Note 2), (Note 3)		5.7	V	1, 2, 3
V_{ILD}	Maximum Low Level Dynamic Input Voltage	$V_{CC} = 5.0V, \text{Load } 50pF / 500\Omega$	(Note 7), (Note 10)		0.8	V	4
V_{IHD}	Minimum High Level Dynamic Input Voltage	$V_{CC} = 5.0V, \text{Load } 50pF / 500\Omega$	(Note 7), (Note 10)	2.2		V	4
V_{OLP}	Quiet Output Maximum Dynamic V_{OL}	$V_{CC} = 5.0V, \text{Load } 50pF / 500\Omega$	(Note 7), (Note 9)		1.5	V	4
V_{OLV}	Quiet Output Minimum Dynamic V_{OL}	$V_{CC} = 5.0V, \text{Load } 50pF / 500\Omega$	(Note 7), (Note 9)		-1.2	V	4

AC Parameters

The following conditions apply, unless otherwise specified.

AC: $C_L = 50pF, R_L = 500\Omega, t_{Rise} = 3.0nS, t_{Fall} = 3.0nS$

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub-groups
t_{PLH}	Propagation Delay	$V_{CC} = 4.5V$	(Note 4), (Note 5), (Note 8)	1.5	7.0	ns	9
			(Note 4), (Note 5), (Note 8)	1.5	7.5	ns	10, 11
t_{PHL}	Propagation Delay	$V_{CC} = 4.5V$	(Note 4), (Note 5), (Note 8)	1.5	7.0	ns	9
			(Note 4), (Note 5), (Note 8)	1.5	7.5	ns	10, 11
t_{OSLH}	Output to Output Skew	$V_{CC} = 4.5V$	(Note 7)		1.0	ns	9, 10, 11
t_{OSHL}	Output to Output Skew	$V_{CC} = 4.5V$	(Note 7)		1.0	ns	9, 10, 11

54ACTQ32–QMLV RH Electrical Characteristics (Continued)

Delta Parameters

The following conditions apply, unless otherwise specified.

Burn-in and operating life test, Delta parameters (+25°C)

Symbol	Parameter	Conditions	Notes	Min	Max	Units	Sub-groups
I_{CCH}	Quiescent supply current		(Note 11), (Note 12)		±100	nA	1
I_{CCL}	Quiescent supply current		(Note 11), (Note 12)		±100	nA	1

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT™ circuits outside databook specifications.

Note 2: Screen tested 100% on each device @ +25°C & +125°C temperature, Subgroup 1, 2, 7 & 8.

Note 3: Sample tested (TM5005, Table 1) on each manufacturing lot @ +25°C, +125°C, & –55°C, Subgroups A1, 2, 3, 7, & 8

Note 4: Screen tested 100% on each device @ +25°C, only. Subgroup A9.

Note 5: Sample tested (TM5005, Table 1) on each manufacturing lot @ +25°C, +125°C, & –55°C temperature, Subgroups A9, 10 & 11

Note 6: Transmission line driving test, guardbanded limits set for +25°C, 2mS duration maximum

Note 7: Guaranteed but not tested. Design characterization data

Note 8: +25°C, & +125°C minimum limits guaranteed for 5.5V by guardbanding 4.5V minimum limits.

Note 9: Maximum number of outputs defined as (n) switching. Data inputs are driven 0V to 3V. One output @ V_{OL}

Note 10: Maximum number of data inputs (n) switching. (n-1) inputs switching 0V to 3V. Input-Under-Test switching 3V to threshold (V_{ILD} , 0V to threshold V_{IHD} , $f = 1\text{MHz}$)


Note 11: These parameters shall be recorded before and after the required burn-in and life tests to determine the delta limits.

Note 12: This limit may not be production tested.

Revision History Section

Date Released	Revision	Section	Originator	Changes
12/14/05	A	New Release, Corporate format. Additions made in conversion: Radiation Features, Delta parameter table in electricals and Notes 11 & 12.	L. Lytle	1 MDS datasheet converted into one Corp. datasheet format. Additions made in conversion: Radiation Features, pg 3, Delta parameter table in electricals and Notes 11 & 12 , pg 6 to reflect SMD. MV54ACTQ32-X Rev 1A0 will be archived.


Physical Dimensions inches (millimeters) unless otherwise noted



**14-Lead Ceramic Dual-In-Line Package (J)
NS Package Number J14A**

J14A (Rev J)

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**14-Lead Ceramic Flatpak (W)
NS Package Number W14B**

W14B (Rev P)

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor manufactures products and uses packing materials that meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.

Leadfree products are RoHS compliant.



National Semiconductor
Americas Customer
Support Center
Email: new.feedback@nsc.com
Tel: 1-800-272-9959

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor
Japan Customer Support Center
Fax: 81-3-5639-7507
Email: jpn.feedback@nsc.com
Tel: 81-3-5639-7560

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Transportation and Automotive	www.ti.com/automotive
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2011, Texas Instruments Incorporated