



SCL4030B



QUAD EXCLUSIVE-OR GATE



$Y = A \oplus B$

SCL4070B

QUAD EXCLUSIVE-OR GATE



$Y = A \oplus B$

STATIC CHARACTERISTICS: ($V_{SS} = 0 V$)

PARAMETER	CONDITIONS	V_{DD} (Vdc)	T_{LOW}^{**}		+25°C			T_{HIGH}^{**}		UNIT
			MIN	MAX	MIN	TYP	MAX	MIN	MAX	
QUIESCENT DEVICE CURRENT I_{DD}	$V_{IN} = V_{SS}$ OR V_{DD}	5		0.05		0.0005	0.05		1.5	μA_{dc}
		10		0.1		0.001	0.1		3.0	
		15		0.2		0.002	0.2		6.0	


Note: $*T_{LOW} = -55^{\circ}C$ for C / H devices, $-40^{\circ}C$ for E / S devices, $**T_{HIGH} = +125^{\circ}C$ for C / H devices, $+85^{\circ}C$ for E / S devices.

DYNAMIC CHARACTERISTICS: ($CL = 50pF, TA = 25^{\circ}C$)

PARAMETER	V_{DD} (Vdc)	MINIMUM	TYPICAL	MAXIMUM	UNIT
PROPAGATION DELAY TIME t_{PLH}, t_{PHL}	5		140	280	ns
	10		65	130	
	15		50	100	
OUTPUT TRANSITION TIME t_{TLH}, t_{THL}	5		100	200	ns
	10		50	100	
	15		40	80	


DIE DRAWING

SCL4030B
58 x 46 mils



DIE DRAWING

SCL4070B
58 x 46 mils



Note: Refer to "SCL4000B SERIES FAMILY SPECIFICATIONS" for remaining Dynamic & Static Characteristics, and, for recommended and maximum operating conditions.