

TYPES SN54ALS11, SN54AS11, SN74ALS11, SN74AS11 TRIPLE 3-INPUT POSITIVE-AND GATES

D2661, APRIL 1982—REVISED DECEMBER 1983

- Package Options Include Both Plastic and Ceramic Chip Carriers in Addition to Plastic and Ceramic DIPs
- Dependable Texas Instruments Quality and Reliability

description


These devices contain three independent 3-input AND gates. They perform the Boolean functions $Y = A \cdot B \cdot C$ or $Y = \overline{A} + \overline{B} + \overline{C}$ in positive logic.

The SN54ALS11 and SN54AS11 are characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ALS11 and SN74AS11 are characterized for operation from 0°C to 70°C .

FUNCTION TABLE (each gate)

INPUTS			OUTPUT
A	B	C	Y
H	H	H	H
L	X	X	L
X	L	X	L
X	X	L	L

logic symbol




Pin numbers shown are for J and N packages.

SN54ALS11, SN54AS11 . . . J PACKAGE

SN74ALS11, SN74AS11 . . . N PACKAGE


(TOP VIEW)



SN54ALS11, SN54AS11 . . . FN PACKAGE

SN74ALS11, SN74AS11 . . . FN PACKAGE

(TOP VIEW)



NC—No internal connection

2

ALS AND AS CIRCUITS

TYPES SN54ALS11, SN74ALS11 TRIPLE 3-INPUT POSITIVE-AND GATES

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage	7 V
Operating free-air temperature range: SN54ALS11	-55 °C to 125 °C	
SN74ALS11	0 °C to 70 °C	

Storage temperature range -65 °C to 150 °C

recommended operating conditions

		SN54ALS11			SN74ALS11			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
I_{OH}	High-level output current			-0.4			-0.4	mA
I_{OL}	Low-level output current			4			8	mA
T_A	Operating free-air temperature	-55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS11			SN74ALS11			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 4.5$ V, $I_I = -18$ mA			-1.5			-1.5	V
V_{OH}	$V_{CC} = 4.5$ V to 5.5 V, $I_{OH} = -0.4$ mA	$V_{CC}-2$			$V_{CC}-2$			V
V_{OL}	$V_{CC} = 4.5$ V, $I_{OL} = 4$ mA	0.25	0.4		0.25	0.4		V
	$V_{CC} = 4.5$ V, $I_{OL} = 8$ mA				0.35	0.5		
I_I	$V_{CC} = 5.5$ V, $V_I = 7$ V		0.1			0.1		mA
I_{IH}	$V_{CC} = 5.5$ V, $V_I = 2.7$ V		20			20		μA
I_{IL}	$V_{CC} = 5.5$ V, $V_I = 0.4$ V		-0.1			-0.1		mA
$I_O‡$	$V_{CC} = 5.5$ V, $V_O = 2.25$ V	-30	-112		-30	-112		mA
I_{CCH}	$V_{CC} = 5.5$ V, $V_I = 4.5$ V	1	1.8		1	1.8		mA
I_{CCL}	$V_{CC} = 5.5$ V, $V_I = 0$ V	1.6	3		1.6	3		mA

†All typical values are at $V_{CC} = 5$ V, $T_A = 25$ °C.

‡The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5$ V to 5.5 V, $C_L = 50$ pF, $R_L = 500$ Ω, $T_A = \text{MIN to MAX}$				UNIT	
			SN54ALS11		SN74ALS11			
			MIN	MAX	MIN	MAX		
t_{PLH}	Any	Y	5	23	5	20	ns	
t_{PHL}	Any	Y	3	12	3	10	ns	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.

**TYPES SN54AS11, SN74AS11
TRIPLE 3-INPUT POSITIVE-AND GATES**

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

recommended operating conditions

Recommended operating conditions			SN54AS11			SN74AS11			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage		4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage			2		2			V
V _{IL}	Low-level input voltage				0.8			0.8	V
I _{OH}	High-level output current				-2			-2	mA
I _{OL}	Low-level output current				20			20	mA
T _A	Operating free-air temperature		-55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS11			SN74AS11			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = -18 mA	-	-1.2	-	-	-1.2	-	V
V _{OH}	V _{CC} = 4.5 V to 5.5 V, I _{OH} = -2 mA	V _{CC} -2	-	-	V _{CC} -2	-	-	V
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 20 mA	-	0.35	0.5	-	0.35	0.5	V
I _I	V _{CC} = 5.5 V, V _I = 7 V	-	-	0.1	-	-	0.1	mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V	-	-	20	-	-	20	mA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V	-	-	-0.5	-	-	-0.5	mA
I _{O+}	V _{CC} = 5.5 V, V _O = 2.25 V	-30	-112	-30	-	-112	-	mA
I _{CCH}	V _{CC} = 5.5 V, V _I = 4.5 V	-	4.3	7	-	4.3	7	mA
I _{CCL}	V _{CC} = 5.5 V, V _I = 0 V	-	11.2	18	-	11.2	18	mA

[†]All typical values are at V_{CC} = 5 V, T_A = 25°C.

†The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5\text{ V}$ to 5.5 V , $C_L = 50\text{ pF}$, $R_L = 500\Omega$, $T_A = \text{MIN to MAX}$				UNIT	
			SN54AS11		SN74AS11			
			MIN	MAX	MIN	MAX		
t_{PLH}	Any	Y	1	6.5	1	6	ns	
t_{PHL}	Any	Y	1	6.5	1	5.5	ns	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.