



# HIGH-SPEED CMOS 8-BIT BUS INTERFACE LATCH TRANSCEIVER

*IDTQS74FCT2543AT/CT*


## FEATURES:

- CMOS power levels: <7.5mW static
- Undershoot clamp diodes on all inputs
- True TTL input and output compatibility
- Ground bounce controlled outputs
- Reduced output swing of 0 to 3.5V
- Built-in 25Ω series resistor outputs reduce reflection and other system noise
- A and C speed grades
- I<sub>OL</sub> = 12mA
- Available in SOIC and QSOP packages


## DESCRIPTION:

The IDTQS74FCT2543T is an 8-bit high-speed CMOS TTL-compatible latched bus transceiver with 3-state outputs. These outputs have 25Ω resistors, useful for driving transmission lines and reducing system noise. The 2543T series parts can replace the 543T series to reduce noise in an existing design. All inputs have clamp diodes for undershoot noise suppression. All outputs have ground bounce suppression. Outputs will not load an active bus when V<sub>CC</sub> is removed from the device.

## FUNCTIONAL BLOCK DIAGRAM



## PIN CONFIGURATION



## ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>

Symbol	Description	Max.	Unit
V <sub>TERM</sub>	Terminal Voltage with Respect to GND	- 0.5 to +7	V
T <sub>STG</sub>	Storage Temperature	- 65 to +150	°C
I <sub>OUT</sub>	DC Output Current Max Sink Current/Pin	120	mA
I <sub>IK</sub>	Input Diode Current, V <sub>IN</sub> < 0	- 20	mA
I <sub>OK</sub>	Output Diode Current, V <sub>OUT</sub> < 0	- 50	mA

### NOTE:

- Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

## CAPACITANCE (T<sub>A</sub> = +25°C, f = 1.0MHz)

Symbol	Parameter <sup>(1)</sup>	Conditions	Typ.	Max.	Unit
C <sub>IN</sub>	Input Capacitance	V <sub>IN</sub> = 0V	8	—	pF
C <sub>OUT</sub>	Output Capacitance	V <sub>OUT</sub> = 0V	8	—	pF

### NOTE:

- This parameter is measured at characterization but not tested.

## PIN DESCRIPTION

Pin Names	Description
$\overline{OEAB}$	A-to-B Output Enable Input (Active LOW)
$\overline{OEBA}$	B-to-A Output Enable Input (Active LOW)
$\overline{CEAB}$	A-to-B Enable Input (Active LOW)
$\overline{CEBA}$	B-to-A Enable Input (Active LOW)
$\overline{LEAB}$	A-to-B Latch Enable Input (Active LOW)
$\overline{LEBA}$	B-to-A Latch Enable Input (Active LOW)
A <sub>0</sub> -A <sub>7</sub>	A-to-B Data Inputs or B-to-A 3-State Outputs
B <sub>0</sub> -B <sub>7</sub>	B-to-A Data Inputs or A-to-B 3-State Outputs

## FUNCTION TABLE <sup>(1)</sup>

Inputs						Outputs		Function
$\overline{CEAB}$	$\overline{CEBA}$	$\overline{LEAB}$	$\overline{LEBA}$	$\overline{OEAB}$	$\overline{OEBA}$	A <sub>x</sub>	B <sub>x</sub>	
H	H	X	X	X	X	Z	Z	Disabled, Hold
X	X	X	X	H	H	Z	Z	Disabled
X	X	H	H	X	X	X	X	Hold
L	X	L	H	L	X	—	A	A to B Latch Transparent
X	L	H	L	X	L	B	—	B to A Latch Transparent
L	X	H	X	L	H	Z	NC	Hold Previous A Data
X	L	X	H	H	L	NC	Z	Hold Previous B Data

### NOTE:

- H = HIGH  
L = LOW  
NC = No change  
X = Don't care  
Z = High-Impedance

## DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

Industrial:  $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ,  $V_{CC} = 5.0\text{V} \pm 5\%$

Symbol	Parameter	Test Conditions		Min.	Typ. <sup>(1)</sup>	Max.	Unit
$V_{IH}$	Input HIGH Level	Guaranteed Logic HIGH Level		2	—	—	V
$V_{IL}$	Input LOW Level	Guaranteed Logic LOW Level		—	—	0.8	V
$\Delta V_T$	Input Hysteresis	$V_{TLH} - V_{THL}$ for all inputs		—	0.2	—	V
$I_{IH}$	Input HIGH Current	$V_{CC} = \text{Max.}$	$0 \leq V_{IN} < V_{CC}$	—	—	$\pm 5$	$\mu\text{A}$
$I_{IL}$	Input LOW Current						
$I_{OZ}$	Off-State Output Current (Hi-Z)	$V_{CC} = \text{Max.}$	$0 \leq V_{IN} \leq V_{CC}$	—	—	$\pm 5$	$\mu\text{A}$
$I_{OR}$	Current Drive	$V_{CC} = \text{Min.}, V_{OUT} = 2V^{(2)}$		50	—	—	mA
$V_{IC}$	Input Clamp Voltage	$V_{CC} = \text{Min.}, I_{IN} = -18\text{mA}, T_A = 25^{\circ}\text{C}^{(2)}$		—	-0.7	-1.2	V
$V_{OH}$	Output HIGH Voltage	$V_{CC} = \text{Min.}$	$I_{OH} = -15\text{mA}$	2.4	—	—	V
$V_{OL}$	Output LOW Voltage	$V_{CC} = \text{Min.}$	$I_{OL} = 12\text{mA}$	—	—	0.5	V
$R_{OUT}$	Output Resistance	$V_{CC} = \text{Min.}$	$I_{OL} = 12\text{mA}$	20	28	40	$\Omega$

### NOTES:

1. Typical values are at  $V_{CC} = 5.0\text{V}$ ,  $T_A = 25^{\circ}\text{C}$ .
2. This parameter is guaranteed but not tested.

## POWER SUPPLY CHARACTERISTICS

Following Conditions Apply Unless Otherwise Specified:

Industrial:  $T_A = -40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ,  $V_{CC} = 5.0\text{V} \pm 5\%$

Symbol	Parameter	Test Conditions <sup>(1)</sup>	Min.	Max.	Unit
$I_{CC}$	Quiescent Power Supply Current	$V_{CC} = \text{Max.}$ freq = 0 $0\text{V} \leq V_{IN} \leq 0.2\text{V}$ or $V_{CC} - 0.2\text{V} \leq V_{IN} \leq V_{CC}$	—	1.5	mA
$\Delta I_{CC}$	Supply Current per Input TTL Inputs HIGH	$V_{CC} = \text{Max.}$ $V_{IN} = 3.4\text{V}^{(2)}$ freq = 0	—	2	mA
$I_{CCD}$	Supply Current per Input per MHz	$V_{CC} = \text{Max.}$ Outputs Open and Enabled One Bit Toggling 50% Duty Cycle Other inputs at GND or $V_{CC}^{(3,4)}$	—	0.25	mA/MHz

FCTL

### NOTES:

1. For conditions shown as Min. or Max., use the appropriate values specified under DC Electrical Characteristics.
2. Per TLL driven input ( $V_{IN} = 3.4\text{V}$ ).
3. For flip-flops,  $I_{CCD}$  is measured by switching one of the data input pins so that the output changes every clock cycle. This is a measurement of device power consumption only and does not include power to drive load capacitance or tester capacitance.
4.  $I_{CC} = I_{QUIESCENT} + I_{INPUTS} + I_{DYNAMIC}$   
 $I_{CC} = I_{CC} + \Delta I_{CC} \text{ DHNT} + I_{CCD} (\text{fCP}/2 + \text{fiNi})$   
 $I_{CC}$  = Quiescent Current  
 $\Delta I_{CC}$  = Power Supply Current for a TTL High Input ( $V_{IN} = 3.4\text{V}$ )  
 $\text{DH}$  = Duty Cycle for TTL Inputs High  
 $\text{NT}$  = Number of TTL Inputs at DH  
 $I_{CCD}$  = Dynamic Current Caused by an Output Transition Pair (HLH or LHL)  
 $\text{fCP}$  = Clock Frequency for Register Devices (Zero for Non-Register Devices)  
 $\text{fi}$  = Input Frequency  
 $\text{Ni}$  = Number of Inputs at  $\text{fi}$   
 All currents are in milliamps and all frequencies are in megahertz.

**SWITCHING CHARACTERISTICS OVER OPERATING RANGE(1)**


Symbol	Parameter <sup>(2)</sup>	74FCT2543AT		74FCT2543CT		Unit
		Min.	Max.	Min.	Max.	
t <sub>PHLB</sub> t <sub>PLHB</sub>	Propagation Delay Transparent Mode An to Bn or Bn to An	2.5	6.5	2.5	5.5	ns
t <sub>PHLL</sub> t <sub>PLHL</sub>	Propagation Delay $\overline{LEBA}$ to An, $\overline{LEAB}$ to Bn	2.5	8	2.5	7	ns
t <sub>PZH</sub> t <sub>PZL</sub>	Output Enable Time $\overline{OEBA}$ or $\overline{OEAB}$ to An or Bn $\overline{CEBA}$ or $\overline{CEAB}$ to An or Bn	2	9	2	8	ns
t <sub>PLZ</sub> t <sub>PHZ</sub>	Output Disable Time $\overline{OEBA}$ or $\overline{OEAB}$ to An or Bn $\overline{CEBA}$ or $\overline{CEAB}$ to An or Bn	2	7.5	2	6.5	ns
t <sub>S</sub>	Set-up Time, HIGH or LOW An or Bn to $\overline{LEBA}$ or $\overline{LEAB}$	2	—	2	—	ns
t <sub>H</sub>	Hold Time, HIGH or LOW An or Bn to $\overline{LEBA}$ or $\overline{LEAB}$	2	—	2	—	ns
t <sub>w</sub>	$\overline{LEBA}$ or $\overline{LEAB}$ Pulse Width LOW	5	—	5	—	ns

**NOTES:**

1. C<sub>LOAD</sub> = 50pF, R<sub>LOAD</sub> = 500Ω unless otherwise noted.
2. Minimums guaranteed but not tested.
3. This parameter is guaranteed by design but not tested.

## TEST CIRCUITS AND WAVEFORMS

### TEST CIRCUITS FOR ALL OUTPUTS



### SWITCH POSITION

Test	Switch
Open Drain	Closed
Disable Low	
Enable Low	
All Other Tests	Open


FCTL

#### DEFINITIONS:

CL = Load capacitance: includes jig and probe capacitance.


RT = Termination resistance: should be equal to ZOUT of the Pulse Generator.

### SET-UP, HOLD, AND RELEASE TIMES




FCTL link

### PULSE WIDTH




FCTL link

### PROPAGATION DELAY



FCTL link

### ENABLE AND DISABLE TIMES




FCTL link

#### NOTES:

1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH
2. Pulse Generator for All Pulses: Rate  $\leq 1.0\text{MHz}$ ;  $t_f \leq 2.5\text{ns}$ ;  $t_r \leq 2.5\text{ns}$

## ORDERING INFORMATION

IDTQS XX FCT XXXX XX  
Temp. Range Device Type Package



**CORPORATE HEADQUARTERS**

2975 Stender Way  
Santa Clara, CA 95054

**for SALES:**

800-345-7015 or 408-727-6116  
fax: 408-492-8674  
[www.idt.com](http://www.idt.com)\*

\*To search for sales office near you, please click the sales button found on our home page or dial the 800# above and press 2.  
The IDT logo is a registered trademark of Integrated Device Technology, Inc.