

SN54HC02, SN74HC02

QUADRUPLE 2-INPUT POSITIVE-NOR GATES

D2684, DECEMBER 1982—REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description


These devices contain four independent 2-input NOR gates. They perform the Boolean functions $Y = A + B$ or $Y = \overline{A} \cdot \overline{B}$ in positive logic.

The SN54HC02 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74HC02 is characterized for operation from -40°C to 85°C .

FUNCTION TABLE (each gate)

INPUTS		OUTPUT
A	B	Y
H	X	L
X	H	L
L	L	H

logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54HC02 . . . J PACKAGE


SN74HC02 . . . D OR N PACKAGE

(TOP VIEW)



SN54HC02 . . . FK PACKAGE

(TOP VIEW)



NC — No internal connection

logic diagram (positive logic)



2

HCMOS Devices

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1982, Texas Instruments Incorporated

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

SN54HC02, SN74HC02 QUADRUPLE 2-INPUT POSITIVE-NOR GATES

2

HCMS Devices

absolute maximum ratings over operating free-air temperature range[†]

Supply voltage, V _{CC}	-0.5 V to 7 V
Input clamp current, I _{IK} (V _I < 0 or V _I > V _{CC})	± 20 mA
Output clamp current, I _{OK} (V _O < 0 or V _O > V _{CC})	± 20 mA
Continuous output current, I _O (V _O = 0 to V _{CC})	± 25 mA
Continuous current through V _{CC} or GND pins	± 50 mA
Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package	300°C
Lead temperature 1.6 mm (1/16 in) from case for 10 s: D or N package	260°C
Storage temperature range	-65°C to 150°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

recommended operating conditions

		SN54HC02			SN74HC02			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC} Supply voltage		2	5	6	2	5	6	V
V _{IH} High-level input voltage	V _{CC} = 2 V	1.5			1.5			
	V _{CC} = 4.5 V	3.15			3.15			
	V _{CC} = 6 V	4.2			4.2			
V _{IL} Low-level input voltage	V _{CC} = 2 V	0	0.3	0	0	0.3	0	V
	V _{CC} = 4.5 V	0	0.9	0	0	0.9	0	
	V _{CC} = 6 V	0	1.2	0	0	1.2	0	
V _I Input voltage		0	V _{CC}	0	0	V _{CC}	0	V
V _O Output voltage		0	V _{CC}	0	0	V _{CC}	0	V
t _t Input transition (rise and fall) times	V _{CC} = 2 V	0	1000	0	0	1000	0	ns
	V _{CC} = 4.5 V	0	500	0	0	500	0	
	V _{CC} = 6 V	0	400	0	0	400	0	
T _A Operating free-air temperature		-55	125	-40	85		85	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V _{CC}	T _A = 25°C			SN54HC02		SN74HC02		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	V _I = V _{IH} or V _{IL} , I _{OH} = -20 μA	2 V	1.9	1.998		1.9		1.9		V
		4.5 V	4.4	4.499		4.4		4.4		
		6 V	5.9	5.999		5.9		5.9		
	V _I = V _{IH} or V _{IL} , I _{OH} = -4 mA	4.5 V	3.98	4.30		3.7		3.84		
V _{OL}	V _I = V _{IH} or V _{IL} , I _{OL} = 20 μA	6 V	5.48	5.80		5.2		5.34		V
		2 V		0.002	0.1		0.1		0.1	
		4.5 V		0.001	0.1		0.1		0.1	
	V _I = V _{IH} or V _{IL} , I _{OL} = 4 mA	6 V		0.001	0.1		0.1		0.1	
I _I	V _I = V _{CC} or 0, I _O = 0	4.5 V		0.17	0.26		0.4		0.33	nA
		6 V		0.15	0.26		0.4		0.33	
	C _i	6 V	± 0.1	± 100		± 1000		± 1000		pF
I _{CC}	V _I = V _{CC} or 0, I _O = 0	6 V		2		40		20		μA

SN54HC02, SN74HC02
QUADRUPLE 2-INPUT POSITIVE-NOR GATES

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 50 \text{ pF}$ (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC}	$T_A = 25^\circ\text{C}$			SN54HC02		SN74HC02		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{pd}	A or B	Y	2 V	45	90		135		115		ns
			4.5 V	9	18		27		23		
			6 V	8	15		23		20		
t_t		Y	2 V	38	75		110		95		ns
			4.5 V	8	15		22		19		
			6 V	6	13		19		16		

C_{pd}	Power dissipation capacitance per gate	No load, $T_A = 25^\circ\text{C}$	22 pF typ
----------	--	-----------------------------------	-----------

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2

HCMLOS Devices