

Male headers in SMD mounting

□ 0.635 mm

art. no.	dim. [mm] C			
SL 10 SMD 040 ...	4.00			
SL 10 SMD 052 ...	5.50			
SL 10 SMD 062 ...	6.70			
SL 10 SMD 078 ...	8.20			
SL 10 SMD 104 ...	10.80			
SL 10 SMD 130 ...	13.40			
please indicate:	<table border="0"> <tr> <td>... no. of contacts one row 4-20</td> <td>... surface S = sel. gold-plated G = gold-plated Z = tin-plated</td> <td>... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)</td> </tr> </table>	... no. of contacts one row 4-20	... surface S = sel. gold-plated G = gold-plated Z = tin-plated	... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)
... no. of contacts one row 4-20	... surface S = sel. gold-plated G = gold-plated Z = tin-plated	... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)		
art. no.	dim. [mm] C			
SL 11 SMD 040 ...	4.00			
SL 11 SMD 052 ...	5.50			
SL 11 SMD 062 ...	6.70			
SL 11 SMD 078 ...	8.20			
SL 11 SMD 104 ...	10.80			
SL 11 SMD 130 ...	13.40			
please indicate:	<table border="0"> <tr> <td>... no. of contacts two rows 4-40</td> <td>... surface S = sel. gold-plated G = gold-plated Z = tin-plated</td> <td>... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)</td> </tr> </table>	... no. of contacts two rows 4-40	... surface S = sel. gold-plated G = gold-plated Z = tin-plated	... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)
... no. of contacts two rows 4-40	... surface S = sel. gold-plated G = gold-plated Z = tin-plated	... packing (option) SM = bar magazine B SM = pick and place pad and bar magazine B TR = pick and place pad and tape and reel (250 pcs/reel)		

... packing (option) - additions:

SL 10 SMD 052-104 ...: ... SM; ... B SM, 4-20 contacts

SL 10 SMD 052-078 ...: ... B TR, 4-12 contacts

SL 11 SMD 052-104 ...: ... SM; ... B SM, 6-40 contacts